

PMI 2000



Pramac PMi series inverter: optimal solution to combine silent operation with less fuel consumption and tension stability; the inverters Pramac stabilize the output tension and supply power for all kinds of equipment. They guarantee maximum efficiency: adjusting the speed according to the required load, our inverters reduce the average fuel consumption.

FEATURES


- Inverter technology: stable power for safe operation of sensitive electronics.
- OHV engine provides consistent power for multiple applications.
- Low-oil level shutdown automatically safeguards engine from damage. •
- Economy mode automatically adjusts the engine speed to the optimum level to provide excellent fuel economy and noise reduction.
 USB ports charges your mobile electronics so you can stay connected.
- · Lightweight and compact.
- Easily transportable by handle.
- · Ideal for applications requiring low noise.



PERFORMANCE		
Frequency	Hz	50
Voltage	V	230
Phase		1
Max Power	Watts	2000
Rated Power	Watts	1600



Engine		
Brand		Pramac
Туре		OHV
Exhaust emission level		Stage V
Operating Speed Nominal	rpm	Variable
Fuel		Petrol
Starting Systems		Recoil
Oil capacity	I	0.45
Low Oil Shutdown		\checkmark



H

Inverter

535

305

460

22

555x310x480

(L) mm

(W) mm

(H) mm

Kg

mm

Autonomy		
Fuel tank capacity		3.5
Fuel consumption @ 50%	l/h	1.2
Running time @ 50%	h	3

Noise level		
Guaranteed noise level (LWA)	dB(A)	89
Noise pressure level @ 7 m	dB(A)	61

GENSET CONTROL

COMMANDS

Alternator

Length

Width

Height

Dry weight

Voltage regulation system

Carton box dimension LxWxH

Dimensional data

- Selector switch: O/I
- Air choke Valve
- Starting handle
- Smart throttle: Economy mode automatically adjusts the engine speed to the optimum level to provide excellent fuel economy and noise reduction.

INSTRUMENTATION:

- Voltmeter, Frequency meter, Wattmeter and Hourmeter (display)
- Outputting energy (indicator light Green)
- Overloading and Oil alarming (indicators light Red)
- PROTECTIONS
- Overload
- Oil Guard
- OUTPUT:
- DC12V 6A
- n°2 USB 5V 2A

SOCKET TYPE

SCHUKO 230V 16A IP44

The information is aligned with the Data file at the time of download. Printed on 23/06/2020 (ID 10146)

©2019 | PR INDUSTRIAL s.r.l. | All rights reserved | Image shown may not reflect actual package. Specifications subject to change without notice







